



## SL630 Max 2 Impact Data Sheet

| Item                           | = | Requirements                                    |
|--------------------------------|---|---|
| Type of Lift                   | = | Anti-Vandal CAT 2                               |
| Contract Load                  | = | 630kg   |
| Number of persons              | = | 8   |
| Contract Speed                 | = | 1.0 m/s - 1.6m/s                                |
| Power system                   | = | Gearless Traction VVVF                          |
| Car Internal Dimensions        | = | 1100mm x 1400mm                                 |
| Car Height                     | = | Up to 2400mm                                    |
| Minimum Car Well Dimensions    | = | 1700mm x 1800mm                                 |
| Minimum Pit Depth              | = | 1250mm  |
| Minimum Headroom               | = | 3400 (to the underside of the lifting facility) |
| Car Entrance type              | = | Automatic 2 Panel Side Opening                  |
| Clear Opening                  | = | 900mm x 2000mm                                  |
| Number of Floors               | = | Up to 18 Floors                                 |
| Maximum Lift Travel            | = | Up to 65000m                                    |
| Position of Entrances          | = | Front Only / Rear / Adjacent                    |
| Machine Room Location          | = | MRL – Machine Room less                         |
| Standard Regulation Compliance | = | EN81- 20, EN81-28, EN81-50, EN81-58, EN81-70    |
| Special Regulation Compliance  | = | EN81.71.2                                       |

