

## SL1600 Impact XL Data Sheet

| Item                  | = | Requirements                           |
|-----------------------|---|--|
| Contract Load         | = | 1600kg                                 |
| Number of persons     | = | 21                                     |
| Contract Speed        | = | 1.0 m/s - 1.6m/s                       |
| Lift Travel           | = | Up to 65000m                           |
| Power system          | = | Traction VVVF                          |
| Car Internal          | = | 1400mm x 2400mm                        |
| Dimensions            |   |  |
| Car Height            | = | 2100mm – 2300mm                        |
| Car Well Dimensions   | = | 2100mm x 2770mm                        |
| Pit Depth             | = | 1300mm                                 |
| Headroom              | = | 3400 up to 4000mm (to the underside of |
|                       |   | the lifting facility)                  |
| Car Entrance type     | = | Automatic                              |
| Clear Opening         | = | 900mm x 2000mm – 1200mm x 2200mm       |
| Number of Floors      | = | Up to 18 Floors                        |
| Position of Entrances | = | Front Only / Rear / Adjacent           |
| Machine Room          | = | MRL – Machine Room less                |
| Location              |   |  |
| Standard Regulation   | = | EN81- 20, EN81-28, EN81-50, EN81-58,   |
| Compliance            |   | EN81-70                                |
| Additional Features   | = | Chequer Plate Floor                    |
|                       |   | Bumper Rails                           |